## **EUROPEAN PATENT OFFICE**

## **Patent Abstracts of Japan**

PUBLICATION NUMBER

02060745

PUBLICATION DATE

01-03-90

APPLICATION DATE

26-08-88

APPLICATION NUMBER

63211923

APPLICANT: NIMURA KAGAKU KOGYO KK;

INVENTOR: ITO KOICHI:

INT.CL.

B32B 27/32 C08L 23/14 C08L 23/16 // B29C 55/12 (C08L 23/14 , C08L 83:04 )

B29K 23:00 B29L 9:00

TITLE

BIAXIALLY STRETCHED DOUBLE-LAYER FILM

ABSTRACT: PURPOSE: To enhance transparency and low temp. heat-sealability by laminating a surface layer of a composition consisting of a specific propylene type polymer resin and a specific amount of specific polydioryanosiloxane gum to at least the single surface of a base layer of a proplylene type polymer.

> CONSTITUTION: A surface layer composition is obtained by compounding 0.1-1.0 pts.wt. of polydiorganosiloxane gum having a polymerization degree (n) of 3500-8000 with 100 pts.wt. of at least one kind of a resin selected from a propylene/ethylene random copolymer resin with ethylene content of 3-8wt.% and a propylene/ethylene/butene-1 random copolymer with ethylene content of 0.5-5wt.% and butene-1 content of 3-25wt.%. In order to laminate this surface layer composition to a biaxially stretched base layer composed of a propylene type polymer, said composition is melted to be extruded to the single surface or both surfaces of the propylene type polymer resin of a base layer to form a sheet which is, in turn, biaxially stretched. This composition is easily laminated uniformly and thinly.

COPYRIGHT: (C)1990,JPO&Japio